

BONANZA

RAW MATERIAL	Brahma Bulls		
HIDE SIZE	50+ SQF (Average)		
THICKNESS	1.1-1.3 mm		
APPROXIMATE WEIGHT	2.50 –3.00 oz. / sqft		
TYPE TANNING	Chrome		
TYPE DYEING	Aniline, Drum-Dyed Through		
TYPE FINISH	Protected		
CLASSIFICATION	Top Grain, Performance+		
RUBBING FASTNESS - DRY	500 cycles - Min. Grade 4, ISO 11640		
RUBBING FASTNESS - WET	150 cycles - Min. Grade 3- 4, ISO 11640		
RUBBING FASTNESS-ART. PERSPIRATION	80 cycles - Min. Grade 3, ISO 11640		
LIGHT FASTNESS (UV)	Min. grade 3, NBR 14392		
DRY ADHESION	Min.: 3 N/cm, ISO 11644		
FLEX RESISTANCE	50,000 cycling, No Breaks, ISO 5402-1		
TEAR STRENGTH	Min: 40 N, ISO 3377-2		
TENSILE TEST	Min: 10 N/mm ² , ISO 3376		
ELONGATION TEST	50% to 80%, ISO 3376		
FLAMMABILITY	Passes Cal Tech Bul. #117		

Price: D	ate:
----------	------



BONANZA

DESCRIPTION

Stylized in the look of distressed leather, produced to exceed industry standards of a protected product. Low maintenance with durability suitable for high-traffic environments.

The point at which two motherloads intersect (Wiktionary.com).

PERFORMANCE QUALITIES

- o Easy to clean with mild soap and water.
- Superior performance against fading and stains.
- o Resists wear in high-traffic applications.

■■ LEATHER CARE

- Keep furniture dust and dirt free. Dusting and vacuuming with a soft brush. Deal with spills and soil gently and quickly (do not rub or scrub). Use a clean cloth or sponge. If necessary, use clean distilled water only and let dry naturally.
- Do not expose to intense heat sources or direct sunlight. Some color fading may occur if the leather is exposed to direct, intense light and heat.
- Do not use solvent or any product involving solvents to clean leather furniture.

COLORS AVAILABLE (21)

	Price:		Date:	
0	Whiskey			
0	Scarlet	o Slate	o Smoke	o Tobacco
0	Palomino	o Redwood	o Rio	 Sandhills
0	Dark Charcoal	 Magnetite 	o Mushroom	o Oatmeal
0	Bone	o Cedar	o Cuero	o Dark Brown
0	Amber	 Bandwagon 	o Bark	o Blackstone